


ORDERING GUIDE FOR THE ELIMINATOR HD ACTUATOR

Ordering Information

H	D				-			-			-			-					-	
----------	----------	--	--	--	---	--	--	---	--	--	---	--	--	---	--	--	--	--	---	--

Base No. (Capacity) HD201 (1,000 lbf) HD302 (2,000 lbf) HD304 (4,000 lbf) HD404 (4,000 lbf) HD406 (6,000 lbf) HD508 (8,000 lbf) HD516 (16,000 lbf) HD518 (18,000 lbf) HD625 (25,000 lbf)	Unit Mounting Option MB: Bottom Mount FF: Front Flange MF: Foot Mount TF: Front Trunnion TR: Rear Trunnion	Motor Position 1, 2, 3, 4 0 = In-Line 	Precision/Lead Accuracy** A: .002 in/ft Zero Backlash B: .0005 in/ft Zero Backlash X: Standard
Std. Stroke Length* 06: 6 in. 12: 12 in. 18: 18 in. 24: 24 in. 30: 30 in. 36: 36 in. 42: 42 in. 48: 48 in.	Rod End Option E: Female Eye F: Female Thread A: Self-Aligning Coupler M: Male Thread S: Spherical Rod Eye	Gearbelt Reduction 00: In-Line/Direct Coupled 10: 1:1 20: 2:1	N.C. Switch Qty 0, 1, 2, 3, etc.
	Configuration L: In-Line U: Parallel Offset	Switch Type A: Hall Sourcing PNP B: Hall Sinking NPN C: Reed D: Switch Track / No Switches X: Solid Cover / No Switches	N.O. Switch Qty 0, 1, 2, 3, etc.

For custom stroke lengths, contact EDrive.

* HD201 is available with stroke lengths up to 12 in.
 HD302 – HD304 are available with stroke lengths up to 36 in.
 HD404 – HD406 are available with stroke lengths up to 42 in.
 HD508 – HD625 are available with stroke lengths up to 48 in.
 ** HD201 – Std. Precision/Lead Accuracy is 0.0005 in/ft, Zero Backlash
 ** HD302, HD404 – Zero Backlash not available